	Amen	dments	To The	Claims:
--	------	--------	--------	---------

This listing of claims will replace all prior versions, and listings, of claims in the application.

<u>Listi</u>	ng of Claims:
1.	(currently amended) Dosage feed device-(1), in particular for the dosage feed of an
addit	ive fluid-(2) in crude oil production, the dosage feed device comprising:
	with a dosing element (4), which can be adjusted by an adjustment device (3), and
	— characterised in that
	—_the dosing element—(4)—exhibits including a dosing gap—(5) and a valve device—(7)
arran	ged following the dosing gapit in the fluid flow direction (6) of fluid flow of the additive
fluid-	(2) .
2.	(currently amended) Dosage feed device according to claim 1,
	— whereineharacterised in that
	— an opening area-(8) of the dosing gap-(5) is variable.
	_un opening area (0) of the dosing gap (3) is variable.
3.	(currently amended) Dosage feed device according to claim 1 one of the previous claims,
	— whereincharacterised in that
	—_the dosing gap—(5) is formed between a dosing cone—(9) and counter element—(10), eby the dosing cone—(9) and counter element—(10) are movable relative to one another.
WIICI	
4.	(currently amended) Dosage feed device according to claim 3 one of the previous claims,
	— whereineharaeterised in that
	—the dosing cone-(9) is formed as the end section-(11) of a displaceable sleeve-(12), the
	end section appearing conical in the direction of fluid flow—(6), whereby at least the end
section	on-(11) is arranged for displacement in a guide sleeve-(13) as the counter element-(10).
5.	(currently amended) Dosage feed device according to claim 1 one of the previous Claims,
- .	(and a serious of the serious of the serious of the provides Clanto,

whereineharacterised in that
———the dosing gap-(5) is formed ring-shaped.
6. (currently amended) Dosage feed device according to claim 4 one of the previous Claims,
whereineharacterised in that
a guide section-(14) of the displaceable sleeve-(12) is supported for displacement in a
support sleeve (15) between an extended position and a withdrawn position (16, 17).
7. (currently amended) Dosage feed device according to claim 6one of the previous claims,
——— wherein characterised in that
————the displaceable sleeve———the displaceable sleeve——the displaceable sleeve—the di
position (177).
O (
8. (currently amended) Dosage feed device according to <u>claim 6 one of the previous claims</u> ,
<u>whereineharacterised in that</u>
an especially annular stop (18) protrudes radially outwards from the displaceable sleeve
(12) for defining the withdrawn position (17) on the support sleeve (15).
9. (currently amended) Dosage feed device according to <u>claim 6 one of the previous claims</u> ,
whereineharacterised in that
——a compression spring—(20) is arranged between the support sleeve—(15) and a first sleeve
end-(19) of the displaceable sleeve-(12).
10. (currently amended) Dosage feed device according to <u>claim 9</u> one of the previous claims,
whereineharacterised in that
a support ring (21) is arranged on the first sleeve end (19).

11. (currently amended) Dosage feed device according to <u>claim 4 one of the previous claims</u> ,
whereincharacterised in that
a valve-seat sleeve (22) is arranged between the valve device (7) and the dosing gap (5) in athe flow channel (23), on which a valve element (24) of the valve device (7) contacts on one side in athe valve-closed position (25).
12. (currently amended) Dosage feed device according to <u>claim 11</u> one of the previous claims ,
<u>wherein</u> eharacterised in that
———the valve device—(7) is a non-return valve—(26) which is subject to spring pressure in the direction of the valve-seat sleeve—(22).
13. (currently amended) Dosage feed device according to <u>claim 11</u> one of the previous claims ,
whereincharacterised in that
the <u>valve element is aessentially</u> spherical valve element—(24) <u>that contacts</u> an opening edge—(27) of the valve-seat sleeve—(22), sealed tightly against fluids, in the valve-closed position (25).
14. (currently amended) Dosage feed device according to <u>claim 11</u> one of the previous elaims,
<u>wherein</u> characterised in that
———a spacer sleeve (28) is arranged between the valve-seat sleeve (22) and the guide sleeve (13).
15. (currently amended) Dosage feed device according to <u>claim 11</u> one of the previous claims ,
——— wherein characterised in that

	-the valve element-(24) is arranged in an essentially cup-shaped element receptacle-(29),
betwee	on which and an inner side (30) of a housing hole (31) at least one fluid opening (51) is
formed	l.
16.	(currently amended) Dosage feed device according to claim 1 one of the previous claims,
	<u>wherein</u> eharaeterised in that
	-the dosing gap (5) exhibits includes a certain opening area (8) in a withdrawn position (17)
of the	displaceable sleeve (12).
17.	(currently amended) Dosage feed device according to claim 14 one of the previous
claims ,	
	<u>wherein</u> eharacterised in that
	-an actuating plunger-(32) is supported for displacement within the displaceable sleeve
(12) , s	pacer sleeve-(28) and valve-seat sleeve-(22), which is in contact with the valve element
(24) at	its support end (33).
18.	(currently amended) Dosage feed device according to claim 17 one of the previous
claims ,	
	<u>whereineharaeterised in that</u>
	-the actuating plunger (32) is movably connected to the adjustment device-(3) with its
moving	g end- (34) remote from its support end -(33) .
19.	(currently amended) Dosage feed device according to claim 18 one of the previous
claims,	
	<u>whereincharacterised in that</u>
	-the movable end-(34) protrudes by a certain delay length-(35) out of the first sleeve end
(19) of	the displaceable sleeve-(12).

20. (currently amended) Dosage feed device according to claim 9 one of the previous claim
whereine haracterised in that
——at least one additive fluid guide—(36) opens into an annular space—(37) of athe fluid channel—(23) between the guide sleeve—(13) and the support sleeve—(15).
21. (currently amended) Dosage feed device according to claim 20 one of the previous elaims,
whereineharacterised in that
——at least one connecting hole-(38) penetrates the support sleeve-(15) in the direction of first sleeve end-(19) from the annular space-(37).
22. (currently amended) Dosage feed device according to claim 1 one of the previous claim whereincharacterised in that
———the adjustment device—(3) exhibits at least a spindle drive—(39), a reduction gear—(40),
particular in the form of a so-called harmonic drive (41), a helically toothed spur gear (42) and drive motor (43).
23. (currently amended) Dosage feed device according to <u>claim 22</u> one of the previously,
——— <u>wherein</u> characterised in that
————the spindle drive-(39) exhibits a rotatable, but axially undisplaceable spindle nut-(44) a a rotationally rigid, but axially displaceable threaded spindle-(45).
24. (currently amended) Dosage feed device according to <u>claim 23</u> one of the previo
<u>wherein</u> eharacterised in that
———a code carrier—(46) of a position sensor—(47) is in particular—assigned to the thread
spindle (45) .

25.	(currently amended) Dosage feed device according to claim lone of the previous claims,
	<u>- wherein</u> eharaeterised in that
	-a device housing-(48) exhibits includes a number of insertion bevels-(49) on the outer side
of its h	ousing (52).